

Be sure. **testo**



Air flow and IAQ measurement improved to the max.

The new universal IAQ instrument testo 400.

Smarter. Faster. Better:

The new generation of air flow and IAQ measurement technology.

Fast on:

Simply exchange probes during the measurement without a re-start.

Measurement assistant:

Smart support for error-free measurement.



To the videos:





Universally applicable:

Wide range of probes for all of your air flow & IAQ measurements.

Always ready to go:


Probes can be calibrated independently of the measuring instrument.

Save time:

Finish measurement with complete documentation directly on site with the customer.

Smarter: Easiest handling.

The new universal IAQ measuring instrument testo 400 and its broad selection of precision probes were developed with just one objective in mind: To make carrying out all measurement tasks in the ventilation and air conditioning sector easier and less complicated for you than ever before.




Everything under control at the touch of a finger

You operate the testo 400 with its Smart-Touch technology just as intuitively as your smartphone.

All data at a glance

You see all measurement data immediately and clearly on the large 5" HD display.



Wireless measurement with one click

You simply start and stop measurements with just one button on the probe handle.

Highly efficient allrounder





And for more demanding measurements, up to eight probes can be used in parallel (4 x Bluetooth, 4 x cable).

Always have the right probe at your fingertips

The flexible Bluetooth and cable probes from the new probe range are completely compatible with each other.

Faster: Save time in documentation and measurement data management.

With the testo 400, you can now carry out worksteps which were previously only possible with a PC and software – directly on site with just one measuring instrument!



Customers and measurement sites are always with you

You can save customers and measurement sites directly in the measuring instrument, manage them and re-use them for repeated measurements.

Digital archive

All measurements are securely stored in the 1.3 GB memory in the instrument. You can retrieve everything quickly thanks to the intelligent search function.

Beat the paperwork


You create professional reports with all relevant data, images and comments directly on site, and you can send them right away by WiFi/Bluetooth.

The App for your PC

The measurement data management and analysis software testo DataControl for the most detailed analysis and reporting in the office is included in delivery.

Better: Error-free results with the measurement data assistant.

With the testo 400, you always have your own personal smart helper with you. The more demanding the measurement, the more the measurement assistant in the instrument supports you in configuration, execution and evaluation of results.



Fast support

The measurement assistant is there to help you in all relevant measurements. Thanks to intuitive menu structures and graphic presentation, you never lose the overview, even with multiple measurement points.



How the measurement assistant supports you in:

IAQ measurement according to EN12599 and ASHRAE 111

Configuration: Input of duct geometry, apertures and measurement points, calculation of measurement depths

Measurement: Graphically guided measurement with all relevant measurement points

Result: Statement of volume flow and the exact measurement inaccuracy



PMV/PPD measurement in accordance with EN ISO 7730 and ASHRAE 55

Configuration: Determination of clothing index and activity

Measurement: Parallel measurement of ambient and radiated temperatures, flow velocity and relative humidity

Result: Statement as a PMV/PPD curve including evaluation




Turbulence measurement acc. to DIN EN 7730

Configuration: Allocation of probes to measurement positions

Measurement: Simultaneous measurement at three heights according to norm

Result: Statement of measurement values at all heights as a value, table and graph.




Improved to the max: Volume flow measurements.

How testo 400 convinces you in ducts and at outlets

- Measurement assistant for volume flow measurement according to norm.
- You have all measurement locations with you at all times and ready at your fingertips.
- Wireless Bluetooth probes for maximum freedom of movement at work.
- You simply finish measurement reports on site – directly with the testo 400.

Duct measurement



Suitable probes



Vane probe
(Ø 16 mm)

Hot wire probe
incl. temperature sensor



Hot wire probe
incl. temperature and humidity sensor



Vane probe
(Ø 16 mm) incl. temperature sensor

Telescope extension
(0.9 m)



Outlet measurement



Telescope and extension for **duct measurements** at heights of up to 5 m – without a ladder.

Suitable probes



Vane probe
(Ø 100 mm) incl.
temperature sensor

High-precision vane probe
(Ø 100 mm) incl.
temperature sensor



testovent 417 - funnel set



Extendable telescope
(37.5 – 100 cm,
including 90°
angle)

Telescope extension
(0.9 m)



testo 400 air flow kits

Components of both kits:

- testo 400 universal IAQ measuring instrument + testo DataControl software
- High-precision humidity/temperature probe head
- 100 mm vane probe head
- 90° angle for connecting vane probes (Ø 100 mm) + handle
- Volume flow case (dimensions: 520 x 410 x 160 mm)



With hot wire probe

- Hot wire probe with telescope (length: 1 m), incl. temperature sensor, with Bluetooth

Order no. 0563 0400 71



With 16 mm vane probe

- 16 mm vane probe with telescope (length: 1 m), incl. temperature sensor, with Bluetooth

Order no. 0563 0400 72




Or

Improved to the max: Comfort level measurements.

testo 400 – first choice for comfort

- Measurement assistant for PMV/PPD measurement and determination of draught rates.
- IAQ data logger for long-term IAQ measurements independently of the instrument.
- Finish report either directly on site or later at a PC.

Comfort level measurement



Suitable probes



CO₂ probe
incl. temperature and humidity sensor



Turbulence probe



Globe thermometer


CO probe



Lux probe




Comfort level measurement



For a reliable measurement, simply attach all required probes to the tripod.

The ideal solution for flexible, long-term IAQ measurements

The IAQ data logger is configured and read out using the testo 400. Up to six probes can then be connected. This results in unheard of measurement possibilities for you – for example, you can now carry out turbulence measurements at three different heights simultaneously.



Our recommendation

testo 400 IAQ and comfort kit with tripod

Comprising:

- testo 400 universal IAQ measuring instrument + testo DataControl software
- CO₂ probe with Bluetooth®, including temperature and humidity sensor
- Turbulence probe
- Globe thermometer
- Measuring tripod
- Transport bag for tripod
- Comfort case



Order no. 0563 0401



IAQ data logger for long-term measurements with the testo 400

Comprising:

- IAQ data logger
- Mains power unit with USB cable

Order no. 0577 0400



Measuring tripod for comfort measurements

Comprising:

- Folding tripod, attachment bar
- 4 x probe holders, incl. bag

Order no. 0554 1591




Improved to the max: Measurements in laboratories, cleanrooms and industry

Always to hand, even for the highest demands

- Highest precision, especially in pressure and temperature measurements.
- Zero-error adjustment in the instrument for even more accurate measurements.
- Display all measurements as a table and graphic curve.

Measurements in cleanrooms and laboratories



The differential pressure sensor of the testo 400 fulfils the accuracy requirements of ISO 14644.

Suitable probes



High-precision vane probe
(Ø 100 mm) incl. temperature sensor



Fume cupboard probe



High-precision humidity/temperature probe




Calibratable immersion/penetration probe (Pt100)



Glass-coated laboratory probe (Pt100)

Industry and production



With the testo 400, you can use up to eight probes simultaneously (4 x Bluetooth, 4 x cable).

Our recommendation

testo 400

Comprising:

- testo 400 universal IAQ measuring instrument + testo DataControl software
- Transport case for volume flow measurements
- Connection hose
- Mains unit with USB cable and calibration protocol



Order no. 0560 0400



Suitable probes for your application

We are happy to advise you personally and individually, in order to find the right probes for your challenges.

Unbeatable duo: The new generation of air flow and IAQ measuring instruments.

With the new testo 400 universal IAQ measuring instrument, the already familiar testo 440 and the universal probe portfolio for both measuring instruments, we are completing our range of innovative climate measuring technology for all requirements.



The compact testo 440

Are you a service engineer, taking care of the general functional testing of air conditioning and ventilation plants? You only document measurement results occasionally, and when you do, you simply want to transfer the data to a PC? Then the testo 440 with its clear display, easy button operation, measurement data store in the instrument, as well as csv. export to your PC, is the ideal choice.

The flexible probe portfolio

The probes cover all air conditioning and ventilation applications and can be used with both the testo 440 and the testo 400. All handles and probes are mutually compatible, allowing you to expand your probe selection as required. Particularly useful: The digital probes can be calibrated independently of the measuring instrument. That means the measuring instrument remains in use and you can carry on working with other probes.

New: The universal testo 400

Are you an expert for complete ventilation systems or for proof of comfort – in accordance with norms? You place the highest demands on precision in cleanrooms, laboratories and industrial applications? Then you can fulfil your complex tasks smarter, faster and better with the testo 400. Thanks to the simplest Smart-Touch operation imaginable, complete data management on site and an intelligent measurement assistant.

Instruments and features in comparison.

	testo 440 dP	testo 400
General		
Colour graphic display	✓	✓ HD display
Operation	Buttons	SmartTouch
Camera	–	✓ Rear camera: 8.0 MP Front camera: 5.0 MP
Magnets on the rear	✓	✓
Integrated differential pressure sensor	✓	✓ High-precision and position-independent
Integrated absolute pressure sensor	–	✓
Compatible with the new Testo probe portfolio	✓ with cable 1x with Bluetooth® 1x	✓ with cable 2x with Bluetooth® 4x
Thermocouple Type K connection	✓ 1x	✓ 2x
Intelligent calibration concept	✓	✓
Zero-error display: Adjustment function at up to 6 measuring points	–	✓
Measurement menus		
Volume flow measurement	✓	✓
Volume flow measurement in accordance with EN 12599 (including measurement uncertainty) and ASHRAE 111	–	✓
Pitot tube measurement	✓ As from 15 m/s	✓ As from 5 m/s
Outlet measurement with funnel	✓	✓
Volume flow measurement using K factor (differential pressure)	✓	✓
Turbulence measurement in accordance with EN ISO 7730	✓	✓ At 3 heights at the same time
PMV/PPD measurement in accordance with EN ISO 7730 and ASHRAE 55	–	✓
NET measurement in accordance with DIN 33403	–	✓ (To follow)
WBGT measurement in line with DIN 33403 and EN ISO 7243	–	✓ (To follow)
Logging mode	✓	✓
Stand-alone, configurable IAQ data logger	–	✓
Measurement data management		
Internal memory (number of measurement values)	✓ (225,000)	✓ (1,000,000)
Customer and measuring point management	–	✓
PC software for analyzing, archiving and documenting measurement data	–	✓
Personalized measurement protocols (including own logo)	–	✓
Integrated camera for on-site documentation	–	✓
On-site printing	✓	✓
Export formats	CSV via USB interface	CSV, PDF, JSON via PC software or directly from the measuring instrument (e-mail or Bluetooth)
Technical data		
Power supply	3x AAA	Li-ion/li-poly rechargeable battery
Dimensions	154 x 65 x 32 mm	210 x 95 x 39 mm
Weight	250 g	500 g

More precision and reliability with the testo 400.

Calibration and test equipment management from Testo Industrial Services

With our subsidiary company Testo Industrial Services, we offer you a competent partner in the field of calibration and test equipment management. Testo Industrial Services has over 200 accredited calibration procedures, making it one of the leading providers of metrological services. A team of qualified, motivated and service-oriented staff allows a high level of quality, with which norms, guidelines and certifications are always fulfilled. The regular calibration of your measuring instruments leads to reliable measurement results for quality assurance.

Unique calibration service



Electrics



Thermodynamics



Mechanics

Measurement
of length

Flow rate



Analysis



Acoustics

- **All from one source:**

New instrument and calibration directly from Testo

- **Broad service portfolio:**

Over 200 calibration procedures according to ISO & DAkkS

- **Holistic test equipment management:**

From the organization to the pick-up and delivery service to calibration

- **Independent of manufacturer:**

Calibration of measuring instruments from all manufacturers

Our recommendation

Regular calibration of measuring instruments is required anywhere they are used in quality-related areas. The digital probes can be calibrated independently of the measuring instrument. That means your universal IAQ measuring instrument testo 400 remains in use and you can carry on working with other probes.

Hassellunden 11A, 2765 Smørum

Tel. 45 95 04 10

info@buhl-bonsoe.dk

www.buhl-bonsoe.dk

www.testo.com